

LIFT SUB

APPLICATION

- Lifting Tools
- BHA manipulation

FEATURES

- One piece
- Industry standard shackle hole
- Box or Pin thread connections available
- Tool joint or service connections

ADDITIONAL INFORMATION

- Tools are manufactured from mild steel as standard. Other materials are available on request.
- Bespoke designs available to suit job specific applications

The WellEnTech Lift Sub is simply used as a device to lift and manipulate tools or bottom hole assemblies at surface during Thru' Tubing operations.

TECHNICAL SPECIFICATION

OD (Inches)	Length (Inches)	Connection	SWL (Tonnes)	Part No.
1.688	7.00	1"AMMT Pin	3	048-1688-ST01
1.750	7.50	1-1/4"AMMT Pin	3	048-1750-ST01
2.125	8.00	1-1/2"AMMT Pin	5	048-2125-ST01
2.875	9.00	2-3/8" PAC Pin	5	048-2875-ST01
3.125	10.00	2-3/8" PAC Pin	5	048-3125-ST01
4.375	11.25	2-7/8" IF Pin	9.5	048-4375-ST02

OPERATION

The Lift Sub has no moving parts and consists of a connection at one end and a hole at the other to suit an industry standard shackle. Ensure the correct size of shackle is fitted to the Lift Sub and that it is securely made up to the tool or tool string. All Lift subs supplied by WellEnTech are load tested and come complete with certification.

