

STRAIGHT BAR

APPLICATION

- Standard fishing operations
- Heavy duty fishing operations
- Jetting peration:
- BHA space out

FEATURES

- One piece
- Various lengths available
- Multi-function operation
- Through bore
- Tool joint or service connections

ADDITIONAL INFORMATION

- Tools are manufactured from mild steel as standard. Other materials are available on request.
- Bespoke designs available to suit job specific applications

OPERATION

The straight bar has no moving parts and consists of a connection at either end of a hollow bar. Other than the correct make—up torque of the connections there is no other operational data.

The WellEnTech Straight bar (often referred to as weight stem) is simply used to add extra mass and/or length to a bottom hole assembly used on a fishing, running or pulling operations.

TECHNICAL SPECIFICATION

OD (Inches)	ID (Inches)	Length (feet)	Tensile Strength (lbs)	Service	Part No.
1.688	0.75	1	62,400	Std	155-1688-ST01
			45,400	H₂S	155-1688-SH01
		2	62,400	Std	155-1688-ST02
			45,400	H₂S	155-1688-SH02
		3	62,400	Std	155-1688-ST03
			45,400	H₂S	155-1688-SH03
		4	62,400	Std	155-1688-ST04
			45,400	H₂S	155-1688-SH04
		5	62,400	Std	155-1688-ST05
			45,400	H₂S	155-1688-SH05
		6	62,400	Std	155-1688-ST06
			45,400	H₂S	155-1688-SH06
2.125	1.00	1	116,500	Std	155-2125-ST01
			84,700	H₂S	155-2125-SH01
		2	116,500	Std	155-2125-ST02
			84,700	H₂S	155-2125-SH02
		3	116,500	Std	155-2125-ST03
			84,700	H₂S	155-2125-SH03
		4	116,500	Std	155-2125-ST04
			84,700	H₂S	155-2125-SH04
		5	116,500	Std	155-2125-ST05
			84,700	H₂S	155-2125-SH05
		6	116,500	Std	155-2125-ST06
			84,700	H₂S	155-2125-SH06
2.875	1.375	1	218,500	Std	155-2875-ST01
			158,900	H₂S	155-2875-SH01
		2	218,500	Std	155-2875-ST02
			158,900	H₂S	155-2875-SH02
		3	218,500	Std	155-2875-ST03
			158,900	H₂S	155-2875-SH03
		4	218,500	Std	155-2875-ST04
			158,900	H₂S	155-2875-SH04
		5	218,500	Std	155-2875-ST05
			158,900	H₂S	155-2875-SH05
		6	218,500	Std	155-2875-ST06
			158,900	H₂S	155-2875-SH06

